www.harisongenerators.com

# -HARISON

0

## NOT JUST BACKUP WE PROVIDE CORE STRENGTH

-HARISON

HARISON

#### SILENT FEATURES OF OUR GENERATORS :

- OPERATABLE FROM MOBILE
- ACOUSTIC ENCLOSURE
- ELECTRONIC GOVERNER
- SILENT & COMPACT
- MULTI FUNCTIONAL
  DIGITAL DISPLAY METER

### Toll Free: 1800 121 5351

-HARISON

### 100 KVA HG100KVA

## MORE THAN JUST BACKUP

## HARISON DIESEL GENERATORS

-HARISON

TOLL FREE : 1800 121 5351

CPCB II

ICAT

ARAI

ORE THAN JUST BACKU

We are certified by

ISO 14001 : 2015

ISO 3046-1:2002

EN/EIC 60034-1:2010

ISO 9001:2015

**ISO 8528** 

ISO 45001:2018

Harison generators is one of the most recognized and successful manufacturer of diesel generators in India. The company's growth is based on a simple approach providing rapid and comprehensive customer service, whatever the requirement and wherever in the globe it may be. Harison's manufacturing plant features industry's leading technology and component handling equipment. Custom designed acoustic testing rooms and pre- delivery testing stations ensure that all the new generators leave the factory ready for the customer. Harison generators is a leading manufacturer of wide range of salient diesel generator with German Technology. Situated in Punjab India, we have constructed a wide and well functional infra-structural unit that plays an important role in the growth of our company. We offer these products at reasonable price and deliver these within the promised time-frame. We provide range from 3.5 kva to 250 kva acoustically enclosed, fully designed and capable of excellent performance on all types of loads. Harison commitment to provide service led solutions has established the company not just as one of the leading genset manufacturers in India, but also as a system designer and an installer, with a team of engineers providing 24/7 maintenance for all types of customers.

100



WE ARE CERTIFIED BY:

ARA



## **TECHNICAL SPECIFICATION FOR DURKATOSERIES**

GENERATOR SET SPECIFICATIONS      PRIME POWER RATING      KW      PHASE      RATED CURRENT      GEN SET MODEL      VOLTAGE      POWER FACTOR      FUEL CONSUMPTION@100%      FUEL CONSUMPTION@75%      FUEL CONSUMPTION@50%      BATTERY STARTING VOLTAGE	100 80 3P 139 HG100KVA 415V(3P) 0.8 23.3 litres/hour 16.7 litres/hour
KW      PHASE      RATED CURRENT      GEN SET MODEL      VOLTAGE      POWER FACTOR      FUEL CONSUMPTION@100%      FUEL CONSUMPTION@75%      FUEL CONSUMPTION@50%	80 3P 139 HG100KVA 415V(3P) 0.8 23.3 litres/hour
PHASE RATED CURRENT GEN SET MODEL VOLTAGE POWER FACTOR FUEL CONSUMPTION@100% FUEL CONSUMPTION@75% FUEL CONSUMPTION@50%	3P 139 HG100KVA 415V(3P) 0.8 23.3 litres/hour
RATED CURRENT GEN SET MODEL VOLTAGE POWER FACTOR FUEL CONSUMPTION@100% FUEL CONSUMPTION@75% FUEL CONSUMPTION@50%	139 HG100KVA 415V(3P) 0.8 23.3 litres/hour
GEN SET MODEL VOLTAGE POWER FACTOR FUEL CONSUMPTION@100% FUEL CONSUMPTION@75% FUEL CONSUMPTION@50%	HG100KVA 415V(3P) 0.8 23.3 litres/hour
VOLTAGE POWER FACTOR FUEL CONSUMPTION@100% FUEL CONSUMPTION@75% FUEL CONSUMPTION@50%	415V(3P) 0.8 23.3 litres/hour
POWER FACTOR FUEL CONSUMPTION@100% FUEL CONSUMPTION@75% FUEL CONSUMPTION@50%	0.8 23.3 litres/hour
POWER FACTOR FUEL CONSUMPTION@100% FUEL CONSUMPTION@75% FUEL CONSUMPTION@50%	0.8 23.3 litres/hour
FUEL CONSUMPTION@75% FUEL CONSUMPTION@50%	
FUEL CONSUMPTION@75% FUEL CONSUMPTION@50%	
	12.8 litres/hour
	12 VDC
ENGINESPECIFICATIONS	HARISON ENGINE
ENGINE MODEL	HG6P7R8M
CAPACITY OF ENGINE	4087 cc
RATED OUTPUT @100%LOAD	99 BHP
NUMBER OF CYLINDERS	4
NO OF STROKES	4
BORE*STROKE	105*118
RATED SPEED	1500
TYPE OF ASPIRATION	Turbo Charged
COOLING SYSTEM	Liquid Cooled
COOLANT CAPACITY	22 LITERS
TYPE OF GOVERNER	Electronic
GOVERNOR CLASS	A1/A2
BATTERY CAPACITY	100 AH
DATTERT CALACITI	10% Overloading is allowed after 10 Hours of continuous
OVERLOAD CAPACITY	running
OIL SUMP CAPACITY	11.5 LITRES
	11.5 EFIRE5
ALTERNATOR SPECIFICATIONS	
MAKE	LEROY SOMER / MECCALTE / STAMFORD
RATING	100 KVA
POWER FACTOR	0.8
ТҮРЕ	Brushless-IP 23
VOLTAGE, VOLTS	415 V (3P)
RATED SPEED	1500 rpm
FREQUENCY,HZ	50Hz
VOLTAGE REGULATIONS	VG 3
CLASS OF INSULATION	H-Class
CONTROL PANEL	With both Inbuilt ATS/AMF and Manual Options
WAVE FORM DISTORTION/TOTAL HARMONIC DISTORTION	No Load<1.5% Non distortion Balanced Linear Load 5%
TELEPHONIC HARMONIC FACTOR	<2%
TELEF HOME HARMONIC FACTOR	\$2.70
ACOUSTICS SPECIFICATIONS	
NOISE LEVEL	<75DBA @1meter distance
LENGTH	2800
WIDTH	1150
	1150
HEIGHT	
FUEL TANK CAPACITY APPROX NET WEIGHT	200 Liters 1400 KG
APPROA NE I WEIGH I	1400 KG

\* Automatic change over switch extra.
 \* Fuel consumptions are noted at standard conditions and may vary than mentioned.

#### MORE THAN JUST BACKUP

## HARISON J SERIES WITH IOT REMOTE OPERATING DEVICE

HARISON

ISON GENERATORS PVT. LTD.

50

00000

DG

15 .

0.989 Diargy 15 na PuelLevel 1500. sty voltage 12 -

240

**BUY NOW** 



HARISON GENERATORS PVT. LTD. Plot No. 81, Daulatpur Industrial Area, Near Focal Point, Near Daulatpur Primary School, Patiala (147002) www.harisongenerators.com | info@harisongenerators.com

Toll Free: 1800 121 5351

