-HARISON

NOT JUST BACKUP WE PROVIDE

CORE STRENGTH

SILENT FEATURES OF OUR **GENERATORS:** OPERATABLE FROM MOBILE

- ACOUSTIC ENCLOSURE
- ELECTRONIC GOVERNER
- SILENT & COMPACT
- DIGITAL DISPLAY METER



Toll Free: 1800 121 5351

320 KVA

HG320KVA

HARISON DIESEL GENERATORS

Harison generators is one of the most recognized and successful manufacturer of diesel generators in India. The company's growth is based on a simple approach providing rapid and comprehensive customer service, whatever the requirement and wherever in the globe it may be. Harison's manufacturing plant features industry's leading technology and component handling equipment. Custom designed acoustic testing rooms and pre- delivery testing stations ensure that all the new generators leave the factory ready for the customer. Harison generators is a leading manufacturer of wide range of salient diesel generator with German Technology. Situated in Punjab India, we have constructed a wide and well functional infra-structural unit that plays an important role in the growth of our company. We offer these products at reasonable price and deliver these within the promised time-frame. We provide range from 3.5 kva to 250 kva acoustically enclosed, fully designed and capable of excellent performance on all types of loads. Harison commitment to provide service led solutions has established the company not just as one of the leading genset manufacturers in India, but also as a system designer and an installer, with a team of engineers providing 24/7 maintenance for all types of customers.



We are certified by ISO 9001:2015 ISO 14001 : 2015

ISO 45001:2018 ISO 3046-1 : 2002 ISO 8528 EN/EIC 60034-1 : 2010 CPCB II ICAT ARAI WE ARE CERTIFIED BY:















TECHNICAL SPECIFICATION FOR DURKATOSERIES

GENERATOR SET SPECIFICATIONS PRIME POWER RATING KW PHASE RATED CURRENT GEN SET MODEL VOLTAGE POWER FACTOR FUEL CONSUMPTION@100% FUEL CONSUMPTION@50% BATTERY STARTING VOLTAGE ENGINESPECIFICATIONS ENGINE MODEL CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	320 256 3P 445 A HG320KVA 415V(3P) 0.8 53.6 litres/hour 40.0 litres/hour 26.9 litres/hour 24 VDC HARISON ENGINE HG14R12M5NIV 8819 cc 258KW (346 BHP) 6 4 114*144
KW PHASE RATED CURRENT GEN SET MODEL VOLTAGE POWER FACTOR FUEL CONSUMPTION@100% FUEL CONSUMPTION@50% BATTERY STARTING VOLTAGE ENGINESPECIFICATIONS ENGINE MODEL CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	256 3P 445 A HG320KVA 415V(3P) 0.8 53.6 litres/hour 40.0 litres/hour 26.9 litres/hour 24 VDC HARISON ENGINE HG14R12M5NIV 8819 cc 258KW (346 BHP) 6 4
PHASE RATED CURRENT GEN SET MODEL VOLTAGE POWER FACTOR FUEL CONSUMPTION@100% FUEL CONSUMPTION@50% BATTERY STARTING VOLTAGE ENGINESPECIFICATIONS ENGINE MODEL CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	3P 445 A HG320KVA 415V(3P) 0.8 53.6 litres/hour 40.0 litres/hour 26.9 litres/hour 24 VDC HARISON ENGINE HG14R12M5NIV 8819 cc 258KW (346 BHP) 6 4
RATED CURRENT GEN SET MODEL VOLTAGE POWER FACTOR FUEL CONSUMPTION@100% FUEL CONSUMPTION@50% FUEL CONSUMPTION@50% BATTERY STARTING VOLTAGE ENGINESPECIFICATIONS ENGINE MODEL CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	445 A HG320KVA 415V(3P) 0.8 53.6 litres/hour 40.0 litres/hour 26.9 litres/hour 24 VDC HARISON ENGINE HG14R12M5NIV 8819 cc 258KW (346 BHP) 6 4
RATED CURRENT GEN SET MODEL VOLTAGE POWER FACTOR FUEL CONSUMPTION@100% FUEL CONSUMPTION@50% FUEL CONSUMPTION@50% BATTERY STARTING VOLTAGE ENGINESPECIFICATIONS ENGINE MODEL CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	445 A HG320KVA 415V(3P) 0.8 53.6 litres/hour 40.0 litres/hour 26.9 litres/hour 24 VDC HARISON ENGINE HG14R12M5NIV 8819 cc 258KW (346 BHP) 6 4
GEN SET MODEL VOLTAGE POWER FACTOR FUEL CONSUMPTION@100% FUEL CONSUMPTION@75% FUEL CONSUMPTION@50% BATTERY STARTING VOLTAGE ENGINESPECIFICATIONS ENGINE MODEL CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	HG320KVA 415V(3P) 0.8 53.6 litres/hour 40.0 litres/hour 26.9 litres/hour 24 VDC HARISON ENGINE HG14R12M5NIV 8819 cc 258KW (346 BHP) 6 4
VOLTAGE POWER FACTOR FUEL CONSUMPTION@100% FUEL CONSUMPTION@75% FUEL CONSUMPTION@50% BATTERY STARTING VOLTAGE ENGINESPECIFICATIONS ENGINE MODEL CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	415V(3P) 0.8 53.6 litres/hour 40.0 litres/hour 26.9 litres/hour 24 VDC HARISON ENGINE HG14R12M5NIV 8819 cc 258KW (346 BHP) 6 4
POWER FACTOR FUEL CONSUMPTION@100% FUEL CONSUMPTION@75% FUEL CONSUMPTION@50% BATTERY STARTING VOLTAGE ENGINESPECIFICATIONS ENGINE MODEL CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	0.8 53.6 litres/hour 40.0 litres/hour 26.9 litres/hour 24 VDC HARISON ENGINE HG14R12M5NIV 8819 cc 258KW (346 BHP) 6 4
FUEL CONSUMPTION@100% FUEL CONSUMPTION@75% FUEL CONSUMPTION@50% BATTERY STARTING VOLTAGE ENGINESPECIFICATIONS ENGINE MODEL CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	53.6 litres/hour 40.0 litres/hour 26.9 litres/hour 24 VDC HARISON ENGINE HG14R12M5NIV 8819 cc 258KW (346 BHP) 6 4
FUEL CONSUMPTION@75% FUEL CONSUMPTION@50% BATTERY STARTING VOLTAGE ENGINESPECIFICATIONS ENGINE MODEL CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	40.0 litres/hour 26.9 litres/hour 24 VDC HARISON ENGINE HG14R12M5NIV 8819 cc 258KW (346 BHP) 6 4
FUEL CONSUMPTION@50% BATTERY STARTING VOLTAGE ENGINESPECIFICATIONS ENGINE MODEL CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	26.9 litres/hour 24 VDC HARISON ENGINE HG14R12M5NIV 8819 cc 258KW (346 BHP) 6 4
BATTERY STARTING VOLTAGE ENGINESPECIFICATIONS ENGINE MODEL CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	24 VDC HARISON ENGINE HG14R12M5NIV 8819 cc 258KW (346 BHP) 6 4
ENGINESPECIFICATIONS ENGINE MODEL CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	HARISON ENGINE HG14R12M5NIV 8819 cc 258KW (346 BHP) 6 4
ENGINE MODEL CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	HG14R12M5NIV 8819 cc 258KW (346 BHP) 6 4
ENGINE MODEL CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	HG14R12M5NIV 8819 cc 258KW (346 BHP) 6 4
CAPACITY OF ENGINE RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	8819 cc 258KW (346 BHP) 6 4
RATED OUTPUT @100%LOAD NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	258KW (346 BHP) 6 4
NUMBER OF CYLINDERS NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	6 4
NO OF STROKES BORE*STROKE RATED SPEED TYPE OF ASPIRATION	4
BORE*STROKE RATED SPEED TYPE OF ASPIRATION	
RATED SPEED TYPE OF ASPIRATION	114*144
TYPE OF ASPIRATION	
	1500
	Turbo Charged Inter Cooled
COOLING SYSTEM	Liquid Cooled
COOLANT CAPACITY	36 LITERS
TYPE OF GOVERNER	Electronic
BATTERY CAPACITY	120 AH X 2
OVERLOAD CAPACITY	10% Overloading is allowed after 10 Hours of continuous
	running
OIL SUMP CAPACITY	19 LITRES
ALTERNATOR SPECIFICATIONS	
MAKE	LEROY SOMER / MECCALTE / STAMFORD
RATING	320 KVA
POWER FACTOR	0.8
ТҮРЕ	Brushless-IP 23
VOLTAGE, VOLTS	415 V (3P)
RATED SPEED	1500 rpm
FREQUENCY,HZ	50Hz
VOLTAGE REGULATIONS	VG 3
CLASS OF INSULATION	H-Class
CONTROL PANEL	With both Inbuilt ATS/AMF and Manual Options
WAVE FORM DISTORTION/TOTAL HARMONIC DISTORTION	No Load<1.5% Non distortion Balanced Linear Load 5%
TELEPHONIC HARMONIC FACTOR	<2%
ACOUSTICS SPECIFICATIONS	
NOISE LEVEL	<75DBA @1meter distance
LENGTH	4300
WIDTH	1400
HEIGHT	1800
FUEL TANK CAPACITY	Equal to or more than 350 Liters
APPROX NET WEIGHT	2850 KG
TATALOG TERRORITA	2000 110

^{*} Automatic change over switch extra.(On Customer Demand and Cost's Extra)
* Fuel consumptions are noted at standard conditions and may vary than mentioned.



HARISON GENERATORS PVT. LTD.

Plot No. 81, Daulatpur Industrial Area, Near Focal Point, Near Daulatpur Primary School, Patiala (147002)

www.harisongenerators.com | info@harisongenerators.com

Toll Free: 1800 121 5351

*: On Customer Demand and Cost's Extra

in association with







